

Fire Extinguisher - Product Specification

Powder - Stored Pressure



Powder extinguishers are suitable for use on Class A, B and also Class C type fires involving flammable gases such as propane and butane. Powder is also highly effective for electrical hazards. This multi-purpose powder interferes with the combustion process and provides rapid fire knock down.

Model	PSP/GP 9/2	PSP/GP 6/2	PSP/GP 4/2	PSP/GP 2/3	PSP/GP 1/3
Capacity (litres)	9	6	4	2	1
Full Weight (kg)	13.1	9.3	6.7	3.7	2.1
Empty Weight (kg)	4.1	3.3	2.7	1.7	1.1
Height (mm)	605	549	445	415	340
Cylinder diameter (mm)	180	160	160	110	86
Minimum Discharge (s)	15	12	9	6	6
Temperature Range (°C)	-20 to 60	-20 to 60	-20 to 60	-20 to 60	-20 to 60
Working Pressure at 20°C	12 bar	12 bar	12 bar	12 bar	12 bar
Test Pressure	25 bar	25 bar	25 bar	25 bar	25 bar
Fire Rating	55 A : 183 B	34 A : 113 B	21 A : 113 B	13 A : 70 B	5 A : 34 B
Kitemark to BS EN 3: 1996	yes	yes	yes	yes	yes

Spare Parts

400-975	Valve assembly	700-535	12 bar pressure gauge	400-868	Safety Pin
400-450	Pull Tite Seal	900-405	Valve O ring	700-079	Hose - 9 kg
700-077	Hose - 6 kg	700-078	Hose - 4 kg	700-620	Nozzle - 2 kg
700-610	Nozzle - 1 kg	400-891	Plastic Boot - 9 l	400-888	Plastic Boot - 6 l
400-500	Bracket - J	700-350	Bracket - spring clip 2 kg	700-360	Bracket - spring clip 1 kg
700-150	Refill - 9 kg	700-140	Refill - 6 kg	700-130	Refill - 4 kg
700-126	Refill - 2 kg	700-125	Refill - 1 kg		

Approvals: BS EN 3 Kitemark Licence KM 32490, BS EN ISO 9001: 2000 FM 32389, PED CE 05PED4667

We reserve the right to change the design and specification without prior notice. May 2006



Certificate No.
FM 32389

